



Putzmeister

Your benefits

- Maximum power – meets all requirements of the current “Stage V” emission category
 - Higher output and more efficient through machine performance management in series
 - Hydraulic mixing unit with overload protection and reverse
 - New robust keypad improves usability
 - Auto-Power-Off – prevents the battery from draining overnight
 - Large diesel tank with 70 litres volume
 - User-friendly operation of feeder lever and air taps
-
- Optimised maintenance and service features
 - Robust design ensures value retention and high resale values
 - Made in Germany

Mixokret M 760 Stage V “Green Efficiency”



Semi-dry
floor screed

- **Cement screed**
- **Calcium sulphate screed (anhydrite)**
- **Magnesia screed**



Special
applications

- Sand
- Aggregate

The M 760 Stage V – Green Efficiency conveys screed up to 190 metres** horizontally and 135 metres** vertically.

The keypad with innovative, colour LED display in the control cabinet makes operation incredibly simple and efficient. The menus for troubleshooting and servicing improve efficiency.

Maximum power and efficiency is available with the Deutz diesel engine (emission category Stage V). The integrated diesel particle filter cleans the exhaust gases and protects our environment from pollution.

For further information related to technical details or application, please contact your local Putzmeister dealer.



Maximum drive power thanks to the 44.5 kW Deutz engine – this meets all requirements of the current „Stage V“ emission category.



User-friendly robust keypad clearly arranged and easy to use – thanks to the „follow the blue light“ principle



Machine performance management in series allows adjustment of engine power as needed. This can save fuel or provide extra power.

Technical data

| M 760 | DH | DHB | DHBS |
|---------------------------|--|-----------------------|-----------------------------------|
| Mixer drum | 260 l, 200 l useful capacity | | |
| Delivery rate* | 4 m ³ /h | 4.8 m ³ /h | 5 m ³ /h |
| Delivery pressure | 8 bar | 8 bar | 8 bar |
| Delivery range** | 190 m horizontally / 135 m vertically (45 storeys) | | |
| Compressor | 4.8 m ³ /min; cut-off pressure 8 bar | | |
| Engine | Diesel, 3-cylinder Deutz with turbocharging, 36.4 kW (emission category Stage V) | | |
| Weight | 1,715 kg | 1,840 kg | 1,900 kg |
| Tank capacity | 70 l | 70 l | 70 l |
| Length | 4,780 mm | 5,075 mm | 5,075 mm |
| Width | 1,480 mm | 1,480 mm | 1,480 mm |
| Height | 1,520 mm | 2,431 mm | 2,431 mm |
| Filling height | 820 mm | 400 mm | 400 mm |
| Maximum grain size | 16 mm | 16 mm | 16 mm |
| Chassis | braked, approved for speeds up to 80 km/h | | |
| Mixing unit | hydraulic with overload protection and reverse | | |
| Special feature | Basis version | with hydraulic feeder | with hydraulic feeder and scraper |

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Optional Standard

Equipment

| | |
|---|-------------------------------------|
| Auto-Power-Off | <input checked="" type="checkbox"/> |
| Car coupling | <input checked="" type="checkbox"/> |
| Central lubrication system | <input checked="" type="checkbox"/> |
| Discharge stand | <input checked="" type="checkbox"/> |
| Fuel gauge in display | <input checked="" type="checkbox"/> |
| Grease pump for lubrication system | <input checked="" type="checkbox"/> |
| Instruction manual and spare parts list | <input checked="" type="checkbox"/> |
| Lever Press with hose | <input checked="" type="checkbox"/> |
| Lifting eye | <input checked="" type="checkbox"/> |
| Performance management | <input checked="" type="checkbox"/> |
| Working lights | <input checked="" type="checkbox"/> |
| Blockage alert | <input type="checkbox"/> |
| Conversion to 100 km/h | <input type="checkbox"/> |
| High-pressure cleaner | <input type="checkbox"/> |
| Light holder 24 V | <input type="checkbox"/> |
| Location system | <input type="checkbox"/> |
| Mixing meter | <input type="checkbox"/> |
| Mixing time adjustment | <input type="checkbox"/> |
| Protection plate for feeder | <input type="checkbox"/> |
| Special canopy paint in RAL colours/ Customer labelling | <input type="checkbox"/> |
| Support feet | <input type="checkbox"/> |
| Toolbox | <input type="checkbox"/> |
| Truck coupling | <input type="checkbox"/> |
| Water dosage (integrated) | <input type="checkbox"/> |
| Wear plates at front end | <input type="checkbox"/> |
| Wear plates at the dome | <input type="checkbox"/> |
| Wear plates (Hardox 6 mm) | <input type="checkbox"/> |
| Wear plates (Hardox 8 mm) | <input type="checkbox"/> |

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
 P.O.Box 2152 · 72629 Aichtal / Germany
 Tel. +49 7127 599-0 · Fax +49 7127 599-743
 mm@putzmeister.com · www.putzmeister.com

