



Putzmeister

Your benefits

- Adjustable delivery rate
- Large hopper ideal for filling from truck mixers
- Integrated 100 bar high-pressure cleaner
- Large toolbox (100 l)
- Central, easily adjustable support leg with low drawbar load
- Sieve with vibrator for improved material flow
- Excellent soundproofing due to sound insulated engine
- Easy access makes all parts easy to service
- Extremely lightweight, impact resistant plastic hood
- CE conformity meets all safety standards in the EU
- Made in Germany

SP 11 THF – Stage V Economical, simple, lightweight



Compliant with Stage V emission standard, the SP 11 THF can easily cover distances of 80 m or heights of 40 m. The sieve and vibrator have been improved to achieve a continuous material flow, even when conveying screed containing plastic or metal fibres. The maximum delivery rate of 15 m³/h and the installed equipment provide all you need to professionally convey self levelling floor screed.

Wear and maintenance parts are easy to access, which makes cleaning and the replacement of wear parts more convenient. You can therefore reduce setup times and increase working productivity.

For further information related to technical details or application, please contact your local Putzmeister dealer.

Self levelling
floor screed

- **Calcium sulphate screed**
(anhydrite)
- **Cement floor screed**





The mechanical 3-cylinder diesel engine from Kubota fulfills the emission standard „Stage V“ and is extremely efficient and easy to maintain. This results in impressively low costs for operation and maintenance.



Operation of the machine directly from the simple and intuitive control panel or via radio remote control.



The large toolbox provides enough space for e.g. remote control, tools, spare parts, water hoses and many other accessories.

Technical data

SP 11 THF – Stage V

Feed hopper	220 l
Pump	Worm pump 2L75
Delivery rate*	0-15 m ³ /h (250 l/min)
Delivery pressure	20 bar
Delivery range**	80 m horizontal, 40 m vertical
Engine	3-cylinder Kubota diesel; 18.5 kW at 3,000 rpm (Stage V)
Weight (fully fuelled)	under 750 kg
Length × width × height	3,260 × 1,420 × 1,160 mm
Filling height	1,000 mm
Maximum particle size	8 mm
Chassis	unbraked, suitable for road use

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Equipment

Car cable adapter	■
Car coupling	■
Cleaning tool	■
Grease cartridge	■
High-pressure cleaner	■
Instruction manual and spare parts list	■
Lever press with hose	■
Seal ring for mortar coupling	■
Standard colour paintwork	■
Standard tool	■
Vibration sieve with 15 mm width (angle section bars)	■
Radio remote control with adjustable delivery rate	□
Special canopy paint in RAL colours	□
Support wheel	□
Truck coupling	□
Vibration sieve with 10 mm mesh opening (mesh grid)	□
Working lights	□

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
P.O.Box 2152 · 72629 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
mm@putzmeister.com · www.putzmeister.com

